

METRIC FELT COMPANY


T E C H N I C A L D A T A

A912-2PT (Part # 2265sl) ANTI-SQUEAK FLOCKED FABRIC PSA

DESCRIPTION

A912-2PT is a high quality flocked fabric designed for demanding automotive interior anti-squeak applications. A912-2PT is coated with a heavy mass of high performance acrylic adhesive, which exhibits excellent adhesion to a wide variety of substrates and has resistance to heat, humidity, solvents and mild plasticizers. The flocked fabric was specifically designed to meet the performance requirements for both GM 6420M and Chrysler MS-JZ8-22.

TAPE CONSTRUCTION



TYPICAL ADHESIVE PERFORMANCE DATA

PEEL ADHESION (PSTC-101)

15 MINUTE APPLIED (oz./in.)	75	-85
24 HOUR APPLIED (oz./in.)	8	5-100

SHEAR ADHESION (PSTC-107)

1" X 1", 1,000 GRAMS, 72 DEGREES F (Hours)	24+
--------------------------------------------	-----

MINIMUM APPLICATION TEMPERATURE	50 DEGREES F
---------------------------------	--------------

NOTE: Performance data indicates average production values from stainless steel and should not be used for minimum specification values. It is required that the converter determines suitability of tape prior to use.

DATE: 8/22/05 jcm

The information contained herein is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.